



6
STANDARD

7B STANDARD



It brings to the attention of all potential customers, all recipients, and to the maximum extent possible, external interlocutors, that Faresin Industries S.p.A. adopts a general Disclaimer regarding the description of the technical and functional characteristics of its machineries, as well as the manner of their use, also with regard to their safety. The Disclaimer must be understood as having a general scope, and therefore Faresin Industries s.p.a. invites to know it, also by accessing the website: www.faresindustries.com



FARESIN.COM



ENGINE STAGE V		3.30	3.36	3.40
Builder		FPT N67	FPT N67	FPT N67
Power	kW/hp	212/290	212/290	212/290
Aftertreatment system		DOC + SCROF	DOC + SCROF	DOC + SCROF
Capacity	ft³	1,059.4	1,271.3	1,412.6

DIMENSIONS ECOMIX		3.30	3.36	3.40
[A] total length	ft	39.4	38.7	39.4
[B] height	ft	11	11.6	12.3
[C] width	ft	8.2	9.2	9.2
[D] milling cutter width	ft	7.2	7.2	7.2
[E] milling height	ft	18.4	21.5	21.5
[F] front unloading height	ft	3.1	3.1	3.1
[G] rear unloading height	ft	3.8	3.8	3.8
[H] outside wheels	ft	8.2	8.2	8.2
[I] axle clearance 1-2	ft	11	11	11
[L] axle clearance 2-3	ft	4.1	4.1	4.1
[M] rear projection	ft	10	10	10
[N] front projection	ft	13.5	13.5	13.5
[O] frame height	ft	2	2	2

WEIGHT				
Unladen weight	lbs	46,297	48,061	48,502

TYRES				
Standard		385/55 R22,5	385/55 R22,5	385/55 R22,5

CONFIGURATION		ECOTRONIC	
Adjustable seat with air suspension		●	
Joystick		multi-function electro-proportional	
Cabin		PF Cab	
Ventilation system		three speeds and temperature setting	
Air conditioning		○	
Steering column with three adjustment points		●	
Front and rear road traffic lights		●	
7 work LED lights		●	
Fuel tank	gal	79	
Electronic weighing system		4 sensor	
Maximum speed	mph	25	
Front axle 1		Adjustable air suspension drive and steering	
Front axle 2		Adjustable and steerable air suspension	
Rear axle		Adjustable air suspension drive and steering	
All-wheel steering		●	
Height-adjustable air suspension and automatic leveling		●	
ABS system		automatic	
ASR system		selected	
Number of augers		3	
Speed range of the auger	rpm	5, 10, 15, 20, 25, 30, 40, 50	
NIR ready		○	
Number of knives		from 9 to 10	
External diameter of milling cutter roller	in	25.6	
Two unloading doors with belt		●	
Hydraulic counter-knives		3	
Shredder on milling cutter		○	
Automatic greasing system		○	

● Standard ○ Optional - Not available