



TECHNICAL SHEET

VERTICAL TRAILED **COMMANDER**

US

It brings to the attention of all potential customers, all recipients, and to the maximum extent possible, external interlocutors, that Faresin Industries S.p.A. adopts a general Disclaimer regarding the description of the technical and functional characteristics of its machineries, as well as the manner of their use, also with regard to their safety. The Disclaimer must be understood as having a general scope, and therefore Faresin Industries s.p.a. invites to know it, also by accessing the website: www.faresindustries.com



Models		Commander 2.30	Commander 2.40
Dimensions			
[A] Total length	in	326	346
[B] Height	in	139	154
[C] Width	in	114	114
[D] Outside wheels	in	94	94
[E] Unloading height	in	28	28
[F] Drawbar axle length	in	188	188
Transmission			
Mechanical transmission		●	●
Required power	kW/hp	96-130	140-190
Power take-off	rpm	1000	1000
Weights			
Capacity	ft ³	1,060	1,415
Unladen weight	lbs	27,556	30,870
Maximum capacity	lbs	26,460	35,269
Mixing tub			
Augers	n.	2	2
2-speed gearbox		●	●
Load sensors	n.	6	6
Tank thickness	in	5/16	5/16
Tank bottom thickness	in	1	1
thickness spiral	in	7/8	7/8
Auger diameter	in	90	98
Number of auger spiral revolutions		3	3.5
Planetary auger reducer	rpm	36@1000	36@1000
Number of knives		11+11	13+13
Stainless steel tank coating		○	○
Manual counter-knives	n.	2	2
Hydraulic counter-knives		○	○
Mechanical / Electric distributor		○	○
Chassis		●	●
Containment ring		-	-
Standard discharge		Sides with fixed direct chute - Direct rear	Sides with fixed direct chute - Direct rear
Axles			
Double axle with balance		●	●
Brakes			
Braking system		○	○
Negative hydraulic / pneumatic / parking brakes		○	○
Other			
Standard tyres		255/70 R22.5	255/70 R22.5

● Standard ○ Optional - Not available

